



**VENTING - SELF FLASHING ACRYLIC SKYLIGHT - THERMALLY BROKEN WITH INSULATED CURB - Specification:**

Venting Self Flashing Acrylic (dome or pyramid as an option) skylights, **ORCA Manufacturing, Inc.**, Model V-SFA-TB, 9 ISC (6" and 12" curbs available as an option) shall be factory assembled units, each consisting of acrylic domes or pyramids, with .072 extruded glazing sash with polyurethane thermal break to prevent condensation on interior portions of aluminum frame and with extruded aluminum glazing retaining angle. Each unit will have a built-in evaporative condensation gutter. Insulated curbs shall be of double wall construction of corrosion resistant aluminum connected at top and bottom with thermal barriers. Units shall have a 3" mounting flange for installation to roof deck. Above is of all welded construction.

NOTE: Glazing materials are NOT designed to support the weight of a person. Fall protection may be required and is available as an option.

Model:   A   x   B   V-SFA-TB, 9ISC, [ Glz ], [ Finish ]



TITLE: VENTING - SELF FLASHING ACRYLIC  
9" INSULATED CURB

Date:	May 01, 2003	
Drawn By:	AP	Sheet:
Rev. By:	CRH	1 of 1
Engineer:	CRH	

ORCA Manufacturing, Inc.  
P.O. Box 2186  
Easton, MD 21601  
Phone: 800-776-1539